



CLEANER CLEANJET U-1012

PROPERTIES

CLEANER CLEANJET U-1012 has low evaporation rate and low chemical profile to be compatible with a majority of printhead models suitable for UV/Solvent/Oil inks and avoiding damages to sensitive parts of printheads. It can wet out small particles that have dried out on printheads using UV/Solvent/Oil based technology inks. The **CLEANER CLEANJET U-1012** has a low viscosity and is therefore recommended for high resolution heads.

PHYSICAL PROPERTIES

Property	Value
Viscosity (cP @ 20°C)	5.20
Temperature range	25 °C a 45 °C
Relative humidity	30-80 %
Transport temperature	-10 °C a 40 °C
Storage temperature	Keep away from direct light and sources of moisture. The product is stable in its original packaging for at least 24 months.

APPLICATION/WAY OF USE

CLEANER CLEANJET U-1012 is a UV/Solvent/Oil cleaning solution for use in head cleaning systems on CLAJECTOR, PURGESTATION, CRIBHEAD and BACKTRACK machines.

SAFETY AND HANDLY

For safety information and product handling instructions, please refer to the safety data sheet available on our website <https://www.personasytecnologia.com/es/cleaner>

The information provided in this Technical Sheet, as well as technical advice or recommendations contained therein, are based on the experience we have gained up until now. However, they are not a legal guarantee of the specific properties of the product nor its suitability for a given application since we cannot cover or anticipate any possible misapplication of our products or their incompatibility with products of third parties. For this reason, our products are supplied without a guarantee for the finished work. We recommend that users carry out their own tests to verify that their own requirements are met. In case of doubt, consult with our Technical Department which will advise you accordingly.