



## CLEANER CLEANJET W-1503T

### PROPERTIES

**CLEANER CLEANJET W-1503T** has a low evaporation rate and a wide compatibility profile so it can be used in a multitude of printheads suitable for water-based inks without risk of incompatibilities or damage to sensitive elements. It has a high solvent capacity that solubilises the residues accumulated on the internal parts of the printheads improving the recovery rate. It generates little foam to maintain a constant flow during recirculation.

### PHYSICAL PROPERTIES

Property	Value
Viscosity (cP @ 25°C)	3.00 – 3.50
Temperature range	25 °C to 30 °C
Relative humidity	30-80 %
Transport temperature	-10 °C to 40 °C
Storage temperature	5 °C to 35 °C

### APLICACION/WAY OF USE

**CLEANER CLEANJET W-1503T** is a low-viscosity, water-base, bluish-coloured cleaning solution for use in CLAJECTOR, PURGESTATION, CRIBHEAD and BACKTRACK machines.

### SAFETY AND HANDLY

For safety information and product handling instructions, please refer to the safety data sheet available on our website <https://www.personasytecnologia.com/en/cleaner-cleanjet/>

The information provided in this Technical Sheet, as well as technical advice or recommendations contained therein, are based on the experience we have gained up until now. However, they are not a legal guarantee of the specific properties of the product nor its suitability for a given application since we cannot cover or anticipate any possible misapplication of our products or their incompatibility with products of third parties. For this reason, our products are supplied without a guarantee for the finished work. We recommend that users carry out their own tests to verify that their own requirements are met. In case of doubt, consult with our Technical Department which will advise you accordingly.